



Specifications Sylvania LED Downlight  
Insaver Slim 225 Aluminium White  
41W 4800lm 70D - 830 Warm White |  
Cutout 225mm - IP44 - Dimmable



[View Product](#)

## General Information

|                          |                              |
|--------------------------|------------------------------|
| SKU                      | 255250                       |
| EAN                      | 5410288305400                |
| manufacturer_code        | 30540                        |
| Brand                    | Sylvania                     |
| Manufacturer Name        | INSV SL IP44 DL 225 4800 830 |
| Any Lamp all-in warranty | 5 Years                      |
| Average Lifetime (h)     | 100000                       |

## Technical Information

|                             |                    |
|-----------------------------|--------------------|
| Emergency Lighting          | No Emergency Unit  |
| Tiltable                    | No                 |
| Technology                  | LED Integrated     |
| Replaces (Watt)             | 2x26               |
| Wattage                     | 41W                |
| Voltage (V)                 | 220-240            |
| Dimmable                    | Dimmable with Dali |
| Colour Code                 | 830 Warm White     |
| Colour temperature (Kelvin) | 3000 Warm White    |
| Colour Rendering (Ra)       | 80-89              |
| Colour of Light             | White              |

|                       |                          |
|-----------------------|--------------------------|
| Light Colour Options  | Single Color             |
| Beam Angle (degree)   | 70                       |
| Luminous Flux (Lumen) | 4800lm                   |
| Lumen per watt        | 117.1                    |
| Power factor          | >0.95                    |
| Unified Glare Rating  | < 22 - for general areas |
| Product Type Category | LED Downlight            |

## Fixture Information

|                        |                        |
|------------------------|------------------------|
| Mounting Method        | Recessed               |
| Cut out (mm)           | 225                    |
| IP-Rating              | IP44                   |
| Impact Protection (IK) | IK07 - 2 joules        |
| Operating Temperature  | -20 to +40             |
| Housing                | Aluminium              |
| Colour of the Fixture  | White                  |
| Fixture Connection     | PI [Push-in connector] |

## Dimensions

|               |     |
|---------------|-----|
| Height (mm)   | 60  |
| Diameter (mm) | 240 |

## Sensor Information

## Why Any-lamp?

Type of sensor

No Sensor



Order from the **largest lighting specialist** in Europe



**Customised** quotation



Up to **7 years warranty**



**Easy** return process

